

GM'S

KAMA

BOOT



EN ISO 20345 SAFETY FOOTWEAR

SB : Basic requirement (innocuousness, comfort, strength, resistance to shocks hazards & compression 200 J)
S1 : SB + closed back + A + E + FO
S1P : S1 + P
S2 : S1 + WRU
S3 : S2 + P + studded sole

MARKING

A : Antistatic footwear
 AN : Ankle protection
 CI : Insulation against cold
 E : Energy absorption in the heel region
 ESD : Electro Static Discharge
 FO : Resistance to fuel oil of outsole
 HI : Insulation against heat
 M : Metatarsal protection
 P : Penetration resistance
 SRA : Slipping resistance on ceramic tile wet with dilute soap solution
 SRB : Slipping resistance on smooth steel with glycerol
 SRC = SRA + SRB
 WR : Water resistant
 WRU : Water resistant upper
 HRO : Heat resistant outsole 300°C

GM//S
By Gaston MILLE



Model	Item Code	Standard	Marking	EUR Sizes	UK Sizes	US Sizes	Net weight/pair (kg) (size 42)	Full height	
Kama	RAMA3	EN ISO 20345	S3 CI	39/48	5,5/12,5	6/13	1,52	28 cm	11 inches

SOLE

- PU dual density
- Steel antiperforation midsole: 1 100 N
- High performance grip: SRC
- Full height: 30 cm

ENVIRONMENT

- Construction
- Heavy duty
- Oil & Gas

UPPER

- 200J composite toecap
- Full grain leather water & oil resistant
- Acrylic lining

FOCUS

- Large fit
- Prehension handles
- Perfect grip on muddy & rocky soils, oily floors



www.gastonmille.com
welcome@gastonmille.fr

GM//S
By Gaston MILLE